

SOURCE LOCK and verified facts

- Only 019lh-supplier-identity-source-0.jpg defines product geometry and visible identity.
- Model/colour: TP-019LH, white. Functions: cooling, heating and air filtration (3-in-1).
- Electrical version: 120 V, 60 Hz, 1300 W.
- Size: 17.5 X 17.5 X 56 cm / 6.9 X 6.9 X 22.1 in.
- Heating setting: 20-35 C / 68-95 F. Sleep specification: below 32 dB.
- Manual verifies 0-9 h timer, wind-speed adjustment, oscillation, cooling/heating modes and included remote.
- Manual states two included filter types: activated carbon and H11.
- No specific contaminant, odor, allergen, replacement-interval or airflow-performance claim is verified.
- Backgrounds, people/pet and airflow are AI-generated/modified; product pixels remain source-locked.

P0 hard-fail gate

- Wrong model, colour, geometry, proportion or key part; AI-redrawn product; altered outlet, control, base, remote or filter.
- Unsupported angle, feature, parameter or claim; impossible support/installation; floating product. Remote/filter may float only inside an explicit white/detail information card.
- Obvious perspective, lighting, colour-temperature, contact-shadow or reflection conflict.
- Severe blur, halo, ragged edge, wavy silhouette, clipping or unreadable/incorrect text.
- Airflow not originating at the real side outlet, or overlapping any person, pet, plant, furniture, curtain, rug or other solid object.

V6.8 corrections to verify

sharp local source - clean silhouette - complete oval foot - touching shadows
transparent real loop opening - airflow tip hidden under the verified side outlet
large airflow stays in clear wall space - remote floats only in an information card









TP-019LH · 3-IN-1

Cooling. Heating. Air filtration.

Three verified functions, clearly shown in one product.

1

COOLING
Blue airflow for warmer days.

2

HEATING
Controlled warmth for colder rooms.



3

AIR FILTRATION
Two filter types are included:
H11 and activated carbon.

Activated carbon · H11
Included filter types; no performance claim.



COOLING MODE

Fresh comfort for warm days.

Verified product height: 22.1 in / 56 cm.



HEATING MODE

Controlled warmth for colder evenings.

Temperature setting range: 20–35°C / 68–95°F.



COOLING MODE · BLADELESS DESIGN

Designed around real family rooms.

Bladeless loop; people and pet stay outside the airflow path.

AIR FILTRATION

Two filter types are included.

Verified in the TP-019LH supplier manual and packshot

1

Activated-carbon filter

Included filter type.
No unverified performance claim.

2

H11 filter

Included filter type.
No unverified performance claim.

Activated-carbon and H11 filter options are included.



EVERYDAY CONTROL

Verified controls and settings.

All facts below are stated in the supplier manual.



Remote included



Cooling mode

Wind-speed control



Heating mode

20–35°C / 68–95°F



Timer

0–9 hours



Oscillation

Oscillation setting



Electrical specification

120 V · 60 Hz · 1300 W

REAL-WORLD SIZE

Compact at 22.1 inches high.

Verified product dimensions: 6.9 × 6.9 × 22.1 inches.

Product size
6.9 × 6.9 × 22.1 in





SLEEP SETTING

A calmer setting after dark.

Sleep-mode specification: below 32 dB.

REAL PRODUCT DETAILS

Thoughtful details, clearly shown.



Outlet slots

Original oval loop and side outlets



Display and controls

Front display with four visible control icons



Remote

Supplied black remote with grouped controls

Required independent review output

do not view another reviewer's score

White-background candidates - decide separately

- 01 Product only, source-locked, pure-white studio background.
- 02 Product plus the verified remote. Catalogue-style floating is explicitly allowed in this card.
- 03 Product plus the complete verified filter set. Use of the white space must be judged.

100-point set score

Product and source consistency	35	also a hard gate
Clarity, crop and text integrity	20	
Scene realism, light, shadow and perspective	20	
Commercial composition and selling-point prominence	15	
Platform adaptability and differentiation	10	

Required sequence

- 1. Images 01-12 table: P0=0/1, exact region, evidence and correction.
 - 2. Separate P0 and pass/fail for white candidates 01, 02 and 03.
 - 3. Five category scores and total /100. End exactly: PASS - publication candidate; REVISE; or FAIL - P0.
- Dual-review gate: both P0=0, average >=85, lower score >=80, and score spread <=8.